

NR Quick Dry Plus Films

Type of Films	T	VLT	VLR	SET	SER	SEA	UVT	GR	SC	E	UF	TSER
NR Charcoal QDP 05	1.5 Mil	6%	6%	44%	7%	49%	<1%	93%	0.66	0.89	1.12	42%
NR Charcoal QDP 15	1.5 Mil	16%	6%	46%	6%	48%	<1%	82%	0.67	0.89	1.12	41%
NR Charcoal QDP 20	1.5 Mil	19%	6%	47%	6%	47%	<1%	79%	0.69	0.89	1.12	40%
NR Charcoal QDP 30	1.5 Mil	30%	6%	53%	6%	41%	<1%	67%	0.74	0.89	1.12	36%
NR Charcoal QDP 40	1.5 Mil	39%	6%	56%	6%	38%	<1%	57%	0.77	0.89	1.12	33%
NR Charcoal QDP 50	1.5 Mil	49%	6%	60%	6%	34%	<1%	46%	0.80	0.89	1.12	30%

- T : Thickness ● VLT : Visible Light Transmittance ● VLR : Visible Light Reflectance ● SET : Solar Energy Transmittance
- SER : Solar Energy Reflectance ● SEA : Solar Energy Absorbance ● UVT : Ultra Violet Transmittance ● GR : Glare Reduction
- SC : Shading Coefficient ● E : Emissivity ● UF : U Factor (BTU /HR./SQ.FT.) ● TSER : Total Solar Energy Rejection